


### Specifications 规格

Nominal Voltage 额定电压	6V	
Rated Capacity(20 hour rate) 20小时率额定容量	4AH	
尺寸 Dimensions ± 1mm	Length 长	70mm(2.75")
	Width 宽	48mm(1.88")
	Height 高	102mm(4.01")
	Total Height (with terminals) 总高含端子	117mm(4.60")
Weight 重量	Approx.0.72kg (1.59lbs)	
Standard Terminal 标准端子	F 1	

### 放电特性 Discharge Characteristics(20°C,68°F)



### Electrical Specifications 电性能

容量 Capacity 77°F(25°C)	20 hour rate (200mA) 20小时率	4AH
	10 hour rate (372mA) 10小时率	3.72AH
	5 hour rate (680mA) 5小时率	3.4AH
	1 hour rate (2.4A) 1小时率	2.4AH
Internal Resistance 内阻	Fully charged battery 充足电	23m Ω
	77°F(25°C)	
Capacity 温度	104°F(40°C)	102%
Affected by 对容量	77°F(25°C)	100%
Temperature 影响	32°F(0°C)	85%
(20 hour rate) 20小时率	5°F(-15°C)	65%
自放电 Self-Discharge 77°F(25°C)	Capacity after 3 month storage	92%
	Capacity after 6 month storage	83%
	Capacity after 12 month storage	65%
充电 (恒压)	循环使用: 首次充电电流低于1.20A 电压: 7.20~7.50V77°F(25°C)	
	浮充使用: 电压6.75~6.90V77°F(25°C)	
	Cycle: Initial Charging Current less than 1.20A Voltage 7.20~7.50V77°F(25°C)	
	Standby: Voltage 6.75~6.90V77°F(25°C)	

### 放电特性 Discharge Characteristics(0°C/32°F,40°C/104°F)

